

Capon's Beamformer

(Minimum Variance

Distortionless Response (MVDR))

## Capon's Beamformer

• idea:

Design an adaptive beamformer for suppressing the noise and the interferences.

⇒ Minimize the power (variance)

$$E\{|\underline{w}^{*T} \cdot \underline{e}|^2\} = \underline{w}^{*T} \cdot \underline{R}_{ee} \cdot \underline{w}$$

at the output of the beamforming network under the constraint of a distortionless response

$$\underline{F}(\varphi) = \underline{w}^{*T} \cdot \underline{a}(\varphi) = 1$$

to a source with the direction of arrival  $\varphi$  resulting in the array manifold vector  $\underline{a}(\varphi)$ .

Remark:  $\underline{w}^*$  will not be normalized

• Using the eigendecomposition

$$\underline{R}_{cc} = \underline{U} \cdot \underbrace{\begin{pmatrix} \lambda_1 & & 0 \\ & \ddots & \\ 0 & & \lambda_N \end{pmatrix}}_{\underline{\Lambda}} \cdot \underline{U}^{*T}$$

and the definition

$$\underline{\Lambda}^{1/2} = \begin{pmatrix} \sqrt{\lambda_1} & & 0 \\ & \ddots & \\ 0 & & \sqrt{\lambda_N} \end{pmatrix}$$

the objective function can be rewritten as

$$\begin{aligned} \underline{w}^{*T} \cdot \underline{R}_{cc} \cdot \underline{w} &= \underbrace{\underline{w}^{*T} \cdot \underline{U} \cdot \underline{\Lambda}^{1/2}}_{\underline{v}^{*T}} \cdot \underbrace{\underline{\Lambda}^{1/2} \cdot \underline{U}^{*T} \cdot \underline{w}}_{\underline{v}} \\ &= \|\underline{v}\|^2 \end{aligned}$$

$\Rightarrow$  Find the minimum square norm  $\|\underline{v}\|^2$  pseudosolution  $\underline{v}$  of the underdetermined linear system of equations

$$\begin{aligned} 1 &= \underline{a}^{*T}(\varphi) \cdot \underline{w} \\ &= \underbrace{\underline{a}^{*T}(\varphi) \cdot \underline{U} \cdot \underline{\Lambda}^{-1/2}}_{\underline{A}} \cdot \underline{v} \end{aligned}$$

- pseudosolution using the right pseudoinverse:

$$\underline{v} = \underline{A}^{*T} \cdot (\underline{A} \cdot \underline{A}^{*T})^{-1} \cdot \underline{1}$$

$$= \Lambda^{-1/2} \cdot \underline{U}^{*T} \cdot \underline{\alpha}(y) \cdot \left( \underline{\alpha}^{*T}(y) \cdot \underline{U} \cdot \Lambda^{-1/2} \cdot \Lambda^{-1/2} \cdot \underline{U}^{*T} \cdot \underline{\alpha}(y) \right)^{-1}$$

$$= \Lambda^{-1/2} \cdot \underline{U}^{*T} \cdot \underline{\alpha}(y) \cdot \underbrace{\left( \underline{\alpha}^{*T}(y) \cdot \underline{U} \cdot \Lambda^{-1} \cdot \underline{U}^{*T} \cdot \underline{\alpha}(y) \right)^{-1}}_{\underline{R}_{\text{cc}}^{-1}}$$

$$= \frac{\Lambda^{-1/2} \cdot \underline{U}^{*T} \cdot \underline{\alpha}(y)}{\underline{\alpha}^{*T}(y) \cdot \underline{R}_{\text{cc}}^{-1} \cdot \underline{\alpha}(y)}$$

- (conjugate complex) weight vector:

$$\underline{w} = \underline{U} \cdot \Lambda^{-1/2} \cdot \frac{\Lambda^{-1/2} \cdot \underline{U}^{*T} \cdot \underline{\alpha}(y)}{\underline{\alpha}^{*T}(y) \cdot \underline{R}_{\text{cc}}^{-1} \cdot \underline{\alpha}(y)}$$

$$= \frac{\overbrace{\underline{U} \cdot \Lambda^{-1} \cdot \underline{U}^{*T}}^{\underline{R}_{\text{cc}}^{-1}} \cdot \underline{\alpha}(y)}{\underline{\alpha}^{*T}(y) \cdot \underline{R}_{\text{cc}}^{-1} \cdot \underline{\alpha}(y)}$$

$$= \frac{\underline{R}_{\text{cc}}^{-1} \cdot \underline{\alpha}(y)}{\underline{\alpha}^{*T}(y) \cdot \underline{R}_{\text{cc}}^{-1} \cdot \underline{\alpha}(y)}$$

not normalized!

- power at the output of the beamforming network:

$$\begin{aligned} P_{\text{Capon}}(\psi) &= \underline{w}^{*T} \cdot \underline{R}_{ee} \cdot \underline{w} \\ &= \frac{\underline{a}^{*T}(\psi) \cdot \underline{R}_{ee}^{-1} \cdot \underline{R}_{ee} \cdot \underline{R}_{ee}^{-1} \cdot \underline{a}(\psi)}{\underline{a}^{*T}(\psi) \cdot \underline{R}_{ee}^{-1} \cdot \underline{a}(\psi) + \underline{a}^{*T}(\psi) \cdot \underline{R}_{ee}^{-1} \cdot \underline{a}(\psi)} \\ &= \frac{1}{\underline{a}^{*T}(\psi) \cdot \underline{R}_{ee}^{-1} \cdot \underline{a}(\psi)} \end{aligned}$$

- beamscan algorithm:

Search for the (local) maxima of the pseudospectrum  $P_{\text{Capon}}(\psi)$ .

```
function phi = capon(Ree, K, d, manifold, linear, varargin)
%CAPON Capon's beamformer (minimum variance distortionless response, MVDR)
% phi: directions of arrival
% Ree: correlation matrix
% K: number of sources
% d: distance of antenna elements normalized to the wavelength
% manifold: antenna array
% linear: limit search range to pi for linear arrays

samples = 1001; % number of samples for plotting the pseudospectrum

N = length(Ree); % number of antenna elements

% Using the array manifold vector the pseudospectrum is computed as 1/(a'*inv(Ree)*a).
% Passing a vector of directions of arrival one obtains a
% vector of samples of the pseudospectrum.
pseudospectrum = @(phi) real(1./sum(conj(manifold(phi,N,d)).*(inv(Ree)*manifold(phi,N,
d)),1));

% determine all local maxima
phi = maxsearch(pseudospectrum, linear);

% select the K largest local maxima
K = min([K, numel(phi)]);
phi = phi(1:K);

% plot the normalized pseudospectrum
figure;
psi = linspace(0, 1, samples)*2*pi;
h = polar(psi, pseudospectrum(psi)./max(pseudospectrum(psi)), '-');
set(h, 'LineWidth', 2);
set(h, 'Color', 'b');
hold on;
for k = 1:K % plot the estimated directions of arrival
    h = polar([phi(k) phi(k)], [0 1], '-');
    set(h, 'LineWidth', 2);
    set(h, 'Color', 'r');
end
title('Pseudospectrum');

end
```

ULA

$N=6$


$d=0.5\lambda$

$G^2=1$

$\varphi_1 = 90^\circ$

power 1

cupon



$\vec{\varphi}_1 = 90^\circ$

ULA

$$N=6$$

$$d=0,5\lambda$$


$$G^2=1$$

$$\varphi_1 = 75^\circ$$

$$\varphi_2 = 105^\circ$$

} equal power ?

capon



$$\vec{\varphi}_1 = 104,95^\circ$$

$$\vec{\varphi}_2 = 75,05^\circ$$

ULA

$N=6$

$d=0,5\lambda$


$G^2=1$

$\varphi_1 = 83^\circ$

$\varphi_2 = 97^\circ$

} equal power 1

capon



$\hat{\varphi}_1 = 84,54^\circ$

$\hat{\varphi}_2 = 95,46^\circ$